

## **PD10 Series**



## FEATURES & BENEFITS

10 gallon volume @5000 and 7500 psig

 ASME U-1A code stamp standard

 ABS & DNV certifications available

Short, compact design

Top repairable

316 SS or Inconel groove inlays available

 All fasteners have corrosion resistant coating

Standard 4-1/16" API Type RTJ For added safety, lifting ears provided on O.D. of
 coverplate

 Protected charging valve and pressure gauge

 High pre-charge capability delivers excellent dampening performance

Nitrile (NBR),
Hydrogenated Nitrile (HNBR)

Diaphragm kits are fully interchangeable with standard industry products



## The PD Series

Tougher, Safer, Stronger...Smarter

PD Series Gas Charged Dampener Fracturing, Well Service & Drilling

MODEL	VOLUME (gallons)	MAWP (psig)	CONNECTION	ADAPTER PLATE MATERIAL	DIAPHRAGM MATERIAL	ASSEMBLY PART #
PD10-5000	10	5000	4-1/16" API 5000 RTJ ★	Carbon Steel (CS)	NBR HNBR	PD1050-01011 PD1050-07011
PD10-7500	10	7500	4-1/16" API 10000 RTJ ★	Carbon Steel (CS)	NBR HNBR	PD1075-01011 PD1075-07011

\* Additional connection sizes and API & ANSI ratings are available upon request.

