

TOP REPAIRABLE PD20 PIPELINE SERIES™

HIGH PERFORMANCE GAS CHARGED DAMPENERS

Designed for the *Transportation of Hazardous Liquids* by Pipeline.

CFR - 2020 - TITLE 49 - VOL 3 - PART 195 COMPLIANT

PPC Dampeners are utilized worldwide in a variety of applications to reduce damaging effects from fluid flow-induced pulsations.

FEATURES:

- **In-Situ Top Repairable**
- Low Profile Design
- 20 Gallon
- 285 & 1440 psi
- SPD20-0285 with 4" ANSI 150 RF Bottom Connection
- PD20-1440 with 4" ANSI 600 RF Bottom Connection
- ASME Section VIII Div. 1 U-Stamped standard
- Precharge Capable to 1440 psi (consult PPC for application-specific)
- Safer Design Using Integrated Lift Lug
- Standard Paint - 2 Coat of Urethane Pipeline White
- Common Diaphragm Kits for Pump Outfitted Equally on Suction and Discharge
- Full Diaphragm Interchangeability with Industry-Recognized Brands

APPLICATIONS:

- Double-Acting Duplex Pumps
- Crude Oil Pipelines
- Slurry Pipelines
- Hydraulic Ore Transport



CONTACT

Phone 972.699.8600

Address 3309 Essex Dr #200
Richardson, TX 75082

performancepulsation.com

sales@performancepulsation.com

Scan to view our website



PPC PERFORMANCE
PULSATION CONTROL

PD20 PIPELINE SERIES™



HIGH PERFORMANCE GAS CHARGED DAMPENERS

Designed for the *Transportation of Hazardous Liquids* by Pipeline.

CFR - 2020 - TITLE 49 - VOL 3 - PART 195 COMPLIANT

PPC Dampeners are utilized worldwide in a variety of applications to reduce damaging effects from fluid flow-induced pulsations.

FEATURES:

- **In-Situ Top Repairable**
- Low Profile Design
- 20 Gallon
- 285 & 1440 psi
- SPD20-0285 with 4" ANSI 150 RF Bottom Connection
- PD20-1440 with 4" ANSI 600 RF Bottom Connection
- ASME Section VIII Div. 1 U-Stamped Standard
- Precharge Capable to 1440 psi (consult PPC for application-specific)
- Safer Design Using Integrated Lift Lug
- Standard Paint - 2 Coat of Urethane Pipeline White
- Common Diaphragm Kits for Pump Outfitted Equally on Suction and Discharge
- Full Diaphragm Interchangeability with Industry-Recognized Brands

BENEFITS:

- Adapted for Large Double Acting Duplex Pump Suction & Discharge
- Easy to Maintenance
- Exceptional Pump & Systems Performance
- ASME & Third Party verified quality
- Standard Pipeline White (other colors available)
- 50% Reduction in Spare Parts Inventory
- Supply Chain Security

