

### SFVM MODELS



### MAGNUM GROOVED 8" TOP MODELS - 600, 900 & 1200 CUBIC INCH



**SFVM-MODELS** 

### STATUS FLOW

### **SFVM-MODEL**

### **600 CUBIC INCH**

### **GAS CAPACITY**

# B A — 8-5/8"—

### SFVM-1500 SERIES

MODEL	HEIGHT A	HEIGHT B	WEIGHT	MAWP (psi)	MOUNTING CONNECTION	CARTRIDGE	MAX CHARGE (nitrogen)
SFVM-1503-F-600	34	36	142	150	3"-150 RF ANSI	SFVM-244	125 (psi gas)
SFVM-1504-F-600	35	37	146	150	4"-150 RF ANSI	SFVM-244	125
SFVM-1506-F-600	35	37	154	150	6"-150 RF ANSI	SFVM-244	125
SFVM-1508-F-600	35	37	171	150	8"-150 RF ANSI	SFVM-244	125

### SFVM-4500 SERIES

MODEL	HEIGHT A	HEIGHT B	WEIGHT	MAWP (psi)	MOUNTING CONNECTION	CARTRIDGE	MAX CHARGE (nitrogen)
SFVM-4503-F-600	35	37	146	450	3"-300 RF ANSI	SFVM-244	125 (psi gas)
SFVM-4504-F-600	35	37	155	450	4"-300 RF ANSI	SFVM-244	125
SFVM-4506-F-600	35	37	175	450	6"-300 RF ANSI	SFVM-244	125
SFVM-4508-F-600	35	37	199	450	8"-300 RF ANSI	SFVM-244	125

★ Dimensions and weights are for reference only. Manufacturer tolerances may cause dimensions to vary slightly. Engineered drawings can be provided upon request.

### STATUS FLOW

### **SFVM-MODEL**

### 900 CUBIC INCH

### **GAS CAPACITY**

# 13-1/2" B A 8-5/8"

### SFVM-1500 SERIES

MODEL	HEIGHT A	HEIGHT B	WEIGHT	MAWP (psi)	MOUNTING CONNECTION	CARTRIDGE	MAX CHARGE (nitrogen)
SFVM-1503-F-900	46	48	181	150	3"-150 RF ANSI	SFVM-364	125 (psi gas)
SFVM-1504-F-900	47	49	185	150	4"-150 RF ANSI	SFVM-364	125
SFVM-1506-F-900	47	49	193	150	6"-150 RF ANSI	SFVM-364	125
SFVM-1508-F-900	47	49	210	150	8"-150 RF ANSI	SFVM-364	125

### SFVM-4500 SERIES

MODEL	HEIGHT A	HEIGHT B	WEIGHT	MAWP (psi)	MOUNTING CONNECTION	CARTRIDGE	MAX CHARGE (nitrogen)
SFVM-4503-F-900	47	49	185	450	3"-300 RF ANSI	SFVM-364	125 (psi gas)
SFVM-4504-F-900	47	49	194	450	4"-300 RF ANSI	SFVM-364	125
SFVM-4506-F-900	47	49	214	450	6"-300 RF ANSI	SFVM-364	125
SFVM-4508-F-900	47	49	238	450	8"-300 RF ANSI	SFVM-364	125

★ Dimensions and weights are for reference only. Manufacturer tolerances may cause dimensions to vary slightly. Engineered drawings can be provided upon request.

### STATUS FLOW

### **SFVM-MODEL**

### 1200 CUBIC INCH

### **GAS CAPACITY**

# 13-1/2" B A - 8-5/8"

### SFVM-1500 SERIES

MODEL	HEIGHT A	HEIGHT B	WEIGHT	MAWP (psi)	MOUNTING CONNECTION	CARTRIDGE	MAX CHARGE (nitrogen)
SFVM-1503-F-1200	58	60	209	150	3"-150 RF ANSI	SFVM-484	125 (psi gas)
SFVM-1504-F-1200	59	61	214	150	4"-150 RF ANSI	SFVM-484	125
SFVM-1506-F-1200	59	61	222	150	6"-150 RF ANSI	SFVM-484	125
SFVM-1508-F-1200	59	61	238	150	8"-150 RF ANSI	SFVM-484	125

### SFVM-4500 SERIES

MODEL	HEIGHT A	HEIGHT B	WEIGHT	MAWP (psi)	MOUNTING CONNECTION	CARTRIDGE	MAX CHARGE (nitrogen)
SFVM-4503-F-1200	59	61	214	450	3"-300 RF ANSI	SFVM-484	125 (psi gas)
SFVM-4504-F-1200	59	61	223	450	4"-300 RF ANSI	SFVM-484	125
SFVM-4506-F-1200	59	61	243	450	6"-300 RF ANSI	SFVM-484	125
SFVM-4508-F-1200	59	61	266	450	8"-300 RF ANSI	SFVM-484	125

★ Dimensions and weights are for reference only. Manufacturer tolerances may cause dimensions to vary slightly. Engineered drawings can be provided upon request.